

CHECKERED FLAG RACING ASSOCIATION

SIGNATURE FORM

Driver	First Name:		Last Name:	
Car	Make:		Model:	
	Run Group:		Color:	
			Year:	
			Number:	

INSTRUCTIONS (read carefully) :

You are entirely responsible for ensuring that your car and driver equipment meets the technical, safety, and competition criteria as described on this form, and is up to the rigors of track driving. CFRA recommends that you have a professional shop carry out the necessary inspection if you do not have the knowledge to do so yourself. A certified NASA inspection shop is a good place to start. After signing and dating this form, bring it to registration at the event where you will receive your registration packet.

Driver Equipment

All drivers and passengers must wear a helmet certified as SNELL 2015 (SA or M), FIA 8860-2004, or SFI 31.1, or newer.

Group R drivers additionally must wear a suit, head and neck restraint, shoes, and gloves conforming to the following certifications:

SUIT: *SFI 3.2A/5 or FIA 8856-2000;*

or SFI 3.2A/1 with fire retardant underwear.

HANS: *SFI 38.1 or FIA 8858*

SHOES and GLOVES: *SFI 3.3/5 or FIA 8856-2000*

HELMET: *SNELL SA2015, FIA 8860-2004, or SFI 31.1, or newer. (Note "SA")*

All other drivers and passengers not wearing the above must wear long pants, a shirt, and closed-toe shoes. A long-sleeved shirt is highly recommended.

Car Display

All cars must display the car number on both sides of the car. The numbers must be 10" tall or more, in a contrasting color.

Guest numbers start with a zero. Members are assigned permanent numbers.

Group R racers and Group R/A qualifiers also require official CFRA logo stickers and CFRA class stickers to participate in racing and qualifying.

The following cars shall display an "X" at least 4" tall on the back:

First-time drivers in Group A; Group B drivers with less than 5 days of track experience; and Group R drivers who do not yet have a full CFRA Race License.

Car Safety Gear

Cars not using harnesses must use factory seat belts in good condition.

Group R cars must have a one-piece (non-folding) design seat and compatible 5- or 6-point harnesses for driver and any passengers, properly installed according to the seat, harness, and neck restraint manufacturers' instructions, and a driver-accessible fire extinguisher or fire suppression system.

4-point factory-installed or 4-point aftermarket roll protection is required for all Group R cars, all cars with slick tires, and all Group A open cars.

Factory-installed roll protection or 4-point aftermarket roll protection is required for all Group B open cars.

Roll protection is recommended but not required for all other cars.

Car Miscellaneous

All loose items must be removed from the car.

Many other items should be inspected or adjusted, including:

Brake pads • Brake fluid • Brake lines • Brake lights • Brake pedal pressure • Wheel bearings • Steering wheel play • Tire condition • Lug nut torque • Hub caps removed • No oil, fuel, or water leaks • Radiator overflow catch • Radiator hoses • Battery and battery hold-down • Positive terminal covered • Seats properly bolted • Gas cap secure • Glass headlights covered with tape

SIGNATURE (read carefully) :

By signing this form, you are stating that your car and driver equipment meet the CFRA requirements, including those stated above; that you understand that CFRA does not perform technical inspections; and that you understand that if your car requires towing off the track you may be responsible for the cost of towing.

DRIVER'S SIGNATURE:

DATE: